

F6 Two-way Radio







- F6-EM earphone / clip microphoneF6-HM hand microphone
- Z Fo-Hivi Hallu Hilcropi



TECHNICAL DATA	F6	FEATURES	
RF output power	0.5 W	· Clear audio quality	· Battery saving mode
Frequency range	446.000 – 446.100 MHz	Automatic noise reduction	Channel annunciation in English
Channels	16	TOT Time-out timer to stop trans-	· · · · · · · · · · · · · · · · · · ·
Audio output	1 W	mitting automatically Monitoring function DCS/CTCSS encoder and decoder prevents interference in the same frequency	language LED shows receipt, transmission and battery status European wide licence and toll-free usable PC programmable (optional):
Accu / operating time	12 V Li-Po 1300 mAh / 12 h – 30 h		
Temperature range	-25 °C to +55 °C		
Dust / water protection	IP 54		
Shock / vibration	MIL STD 810 C/D/E & TIA/EIA 603		
Working ranges		Housing made of die-cast and	· Frequency, functions and set-
outside, open terrain	5 km	high-resistant plastic	tings can be set by the optional
outside, area between buildings	3 km	Powerful lithium polymer programming software	
		rechargeable battery	, ,
OPTIONAL ACCESSORIES F6-HM MICROPHONE	OPTIONAL ACCESSORIES F6-EM EARPHONE	SUPPLIED WITH	
ARTNO. 870100	ARTNO. 870150	ARTNO. 870000	
· F6-HM hand microphone with	· F6-EM earphone / clip microphone	Two-way radio Rechargeable battery	