

# FL 300HV-G EasyGRADE

## The easiest grade laser



### TECHNICAL DATA

|  |                               |
|--|-------------------------------|
| Self-levelling range                           | ±5°                           |
| Laser class                                    | 2                             |
| Visible laser beam                             | rED                           |
| Horizontal accuracy                            | ± 0.75 mm / 10 m              |
| Vertical accuracy                              | ± 1 mm / 10 m                 |
| <b>Working range with receiver (diameter)</b>  |                               |
| with FR 45                                     | 1200 m                        |
| with FR-DIST 30                                | 600 m                         |
| with FR 77-MM                                  | 600 m                         |
| 90° plumb beam up                              | yes                           |
| <b>Slope setting / axis direction</b>          |                               |
| <b>HORIZONTAL</b>                              |                               |
| Grade setting in X-Axis                        | + 0.1 to 6.9% (at 0.1 % step) |
| Y-Axis self-levelled -or- manual grade setting | ±5° (±9%)                     |
| <b>VERTICAL</b>                                |                               |
| Vertical axis direction                        | ±5°                           |
| 2nd axis self-levelled                         |                               |
| Automatic TILT function                        | yes                           |
| VWS  | yes                           |
| Remote control working range                   | IR 100 m                      |
| Rotating speed                                 | 800 rpm                       |
| Operating time                                 | 40 h Li-Ion                   |
| Temperature range                              | -10° to +50°                  |
| Dust / water protection                        | IP 66                         |

### FEATURES

#### HORIZONTAL

- Self-levelling
- Numerical grade setting in X-Axis
- Manual grade setting in Y-Axis with remote control

#### VERTICAL

- Self-levelling
- Axis direction in Y-Axis with remote control

- TILT function
- VWS function (Vibration-Wind-Security)
- 90° beam to zenith
- Dust / water protection IP 66

#### SUPPLIED WITH FL 300HV-G EASYGRADE + FR 50

ART.-NO. 214055

- Receiver FR 50 with clamp
- Remote control
- Rechargeable battery (Li-Ion)
- Intelligent battery charger
- Battery case for alkaline batteries
- Floor / wall mount (integrated)
- Carrying case

#### SUPPLIED WITH FL 300HV-G EASYGRADE + FR 60-MM

ART.-NO. 214060

- Receiver FR 60-MM with clamp
- Remote control
- Rechargeable battery (Li-Ion)
- Intelligent battery charger
- Battery case for alkaline batteries
- Floor / wall mount (integrated)
- Carrying case

#### SUPPLIED WITH FL 300HV-G EASYGRADE + FR 80-MM

ART.-NO. 214080

- Receiver FR 80-MM with clamp
- Remote control
- Rechargeable battery (Li-Ion)
- Intelligent battery charger
- Battery case for alkaline batteries
- Floor / wall mount (integrated)
- Carrying case