

FL 105H

Quick and easy to use - now even better



TECHNICAL DATA		FL 105H	FEATURES	SUPPLIED WITH FL 105H (LC 2) + FR 50
Self-levelling		horizontal	Self-levelling horizontal rotating laser · 3 buttons for user-friendly functionality · Working range 600 m diameter · Dust / water protection IP 65 · Automatic TILT alarm function · VWS function (Vibration-Wind-Security) · Auto-shut-off when out of level	ART.-NO. 212050 · Receiver FR 50 with clamp for levelling staff · Rechargeable battery and charger · Battery compartment for alkaline batteries · Container
Self-levelling range		±5°		
Laser class		2		
Visible laser beam		red		
Accuracy horizontal		1,0 mm / 10 m		
Working range with receiver Ø				
with FR 45		600 m		
with FR 77-MM		300 m		
Automatic TILT function		yes		
VWS function		yes		
Rotating speed rpm		800		
Operating time		36 h NiMH		SUPPLIED WITH FL 105H (LC 2) + FR 60-MM ART.-NO. 212060 · Receiver FR 60-MM with clamp for levelling staff · Rechargeable battery and charger · Battery compartment for alkaline batteries · Container
Temperature range		-20° to +50°C		SUPPLIED WITH FL 105H (LC 2) + FR 80-MM ART.-NO. 212080 · Receiver FR 80-MM with clamp for levelling staff · Rechargeable battery and charger · Battery compartment for alkaline batteries · Container
Dust / water protection		IP 65		