



FL 155H-G

Dual grade laser for beginners



TECHNICAL DATA	FL 155H-G
Self-levelling range	±6°
Laser class	2
Accuracy	± 0.5mm / 10m
Working range with receiver (Ø)	
with FR 45	1200 m
with FR 77-MM	600 m
Horizontal slope setting	
X-Axis	± 10.000%
Y-Axis	± 10.000%
X and Y-Axis	Σ ± 14 %
Rotating speed	600 rpm
Operating time	30 h
Power supply	Li-Ion
RF Remote control range	80 m
Temperature range	-20°C to +50°C
Dust / water protection	IP 65
Weight (instrument only)	2.2 kg

FEATURES
<ul style="list-style-type: none"> · Horizontal Dual Grade Laser · Digital grade adjustment · Monitored grade · Automatic TILT function · VWS function combined with TILT function · Illuminated display · Zonal control (masking) · Zonal control (electronic beam screen) · Remote control screen · Li-Ion battery technology · Battery charger includes adapter for in-car charging

SUPPLIED WITH
FL 155H-G + FR 60-MM
ART.-NO. 213160
<ul style="list-style-type: none"> · Receiver FR 60-MM with clamp · 2-Way RF Remote control · Li-Ion battery · Intelligent battery charger · Battery case for alkaline batteries · Carrying case

SUPPLIED WITH
FL 155H-G + FR 80-MM
ART.-NO. 213180
<ul style="list-style-type: none"> · Receiver FR 80-MM with clamp · 2-Way RF Remote control · Li-Ion battery · Intelligent battery charger · Battery case for alkaline batteries · Carrying case