

FVE 150 Video Borescope



TECHNICAL DATA	FVE 150	FEATURES	SUPPLIED WITH FVE 150
			ART.-NO. 800710
Camera head		<ul style="list-style-type: none"> · Water proof camera head and probe · 1 m long flexible gooseneck probe with camera head for the optical inspection of inaccessible areas · Camera head with LED lighting · Immediate transfer of the colour image to the large LCD display · 180° image rotation at the press of a button · Internal memory or SD-card to store images and video sequences · 4 GB SD-card included (supports up to 8 GB) · Date and time indication on the display · Transmission of video clips / images onto television or PC for editing or documentation · Multi-language menu (DE, EN, FR, ES, IT, FI) · Accessories: see FVE 100 	<ul style="list-style-type: none"> · Video borescope · 1 m flexible gooseneck probe · TV cable · USB cable · Charger · Magnet · Hook · Mirror · 4 GB SD-card · Container
Viewable angle	0° and 180°		
Focal length	6–7 cm		
Viewable distance	5–15 cm		
Diameter of camera head	17 mm		
Light source	LED		
Display			
Display size	3.2"		
Resolution	320 x 240 pixel		
Image transmission to LCD	Flexible gooseneck		
CMOS Image sensor	300.000 pixel		
Video output (to TV)	PAL / NTSC		
Picture / video formats	JPG / 3 GP		
Resolution picture / video	320 x 240 Pixel		
Various			
Internal memory	70 MB		
Additional memory	4 GB SD-card supports up to 8 GB (optional)		
Operation languages	EN, FR, DE, ES, IT, FI		
Probe length	100 cm		
Bend radius of probe	6 cm		
Dust / water protection probe / camera	IP 67		
Power supply	3.7 V / 2000 mAh Li-Ion		
Operating time	4 h		
Temperature range	-10 °C to + 50 °C		
Humidity range	15 % – 85 % RH		
Dimensions	240 x 160 x 100 mm		
Weight with probe	0.584 kg		